

PRODUCT DATA SHEETS

Base Grille Water Filtration System Model WF-L200V/L200V Capacity 200 Gallons (757 Liters) Model WF-NL120V/NL120V Capacity 120 Gallons (454 Liters)



System tested and certified by NSF International against NSF/ANSI Standard 42, 53 and CSA B483.1 for the reduction of contaminants specified on the Performance Data Sheet.

This system has been tested according to NSF/ANSI 42, 53 and CSA B483.1 for the reduction of the substances listed below. The concentration of the indicated substances in water entering the system was reduced to a concentration less than or equal to the permissible limit for water leaving the system, as specified in NSF/ANSI 42, 53 and CSA B483.1.

| Substance Reduction Aesthetic Effects | Influent Challenge Concentration | Maximum Permissible Product Water Concentration | Average % Reduction |
|---|--|--|---------------------|
| Chlorine Taste/Odor Particulate Class I* | 2.0 mg/L ± 10% At least 10,000 particles/mL | ≥50% ≥85% | 97.5% 99.6% |

| Contaminant Reduction | Influent Challenge Concentration | NSF Reduction Requirements | Average % Reduction |
|--|--------------------------------------|----------------------------|------------------------|
| Lead: @ pH 6.5 Lead: @ pH 8.5 | 0.15 mg/L ± 10% 0.15 mg/L ± 10% | 0.01mg/L 0.01mg/L | 99.3% 98.6% |
| Mercury: @ pH 6.5 Mercury: @ pH 8.5 | 0.006 mg/L ± 10% 0.006 mg/L ± 10% | 0.002 mg/L 0.002 mg/L | 96.4% 85.2% |
| Benzene | 0.015 mg/L ± 10% | 0.0050 mg/L | 93.7% |
| Ethylbenzene | 2.1 mg/L ± 10% | 0.7 mg/L | 99.8% |
| p-dichlorobenzene | 0.225 mg/L ± 10% | 0.075 mg/L | 93.3% |
| O-Dichlorobenzene | 1.8 mg/L ± 10% | 0.6 mg/L | 99.9% |
| Toxaphene | 0.015 mg/L ± 10% | 0.003 mg/L | 93.1% |
| 1,2,4-Trichlorobenzene | 0.21 mg/L ± 10% | 0.07 mg/L | 99.7% |

Test Parameters: pH = 7.5 ± 0.5 unless otherwise noted. Flow = 0.5 gpm (1.9 Lpm). Pressure = 60 psig (413.7 kPa). Temp. = 63°F (17.2°C).


- It is essential that operational, maintenance, and filter replacement requirements be carried out for the product to perform as advertised.
- Model WF-L200V:** The filter monitor system measures the amount of water that passes through the filter and alerts you to replace the filter. When 90% of the filter's rated life is used, the filter indicator light changes from green to yellow. When 100% of the filter's rated life is used, the filter indicator light changes from yellow to red, and it is recommended that you replace the filter. Use replacement cartridge L200V / NL120V, part #4396702, EDR6D1. 2015 suggested retail price of \$49.99 U.S.A./\$49.99 Canada. Prices are subject to change without notice.

Model WF-NL120V: Change the water filter cartridge every 6 months. Use replacement cartridge L200V / NL120V, part #4396702, EDR6D1. 2015 suggested retail price of \$49.99 U.S.A./\$49.99 Canada. Prices are subject to change without notice.

- The product is for cold water use only.
- Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.
- Refer to the front cover or "Accessories" section for the Manufacturer's name, address and telephone number.
- Refer to the "Warranty" section for the Manufacturer's limited warranty.

Application Guidelines/Water Supply Parameters

| | |
|-------------------|---------------------------------|
| Water Supply | Potable City or Well |
| Water Pressure | 30 - 120 psi (207 - 827 kPa) |
| Water Temperature | 33° - 100°F (0.6° - 37.8° C) |
| Service Flow Rate | 0.5 GPM (1.89 L/min.) @ 60 psi. |



*Class I particle size: ≥0.5 to < 1.0 µm
 **Test requirement is at least 10,000 particles/mL of AC Fine Test Dust.
 ***These contaminants are not necessarily in your water supply.
 Performance may vary based on local water conditions.
 © NSF is a registered trademark of NSF International.